

CTA Standard

High Definition TV Analog Component Video Interface

CTA-770.3-E

(Formerly CEA-770.3-E)

June 2013



**Consumer
Technology
Association™**

NOTICE

Consumer Technology Association (CTA)TM Standards, Bulletins and other technical publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards, Bulletins and other technical publications shall not in any respect preclude any member or nonmember of the Consumer Technology Association from manufacturing or selling products not conforming to such Standards, Bulletins or other technical publications, nor shall the existence of such Standards, Bulletins and other technical publications preclude their voluntary use by those other than Consumer Technology Association members, whether the standard is to be used either domestically or internationally.

Standards, Bulletins and other technical publications are adopted by the Consumer Technology Association in accordance with the American National Standards Institute (ANSI) patent policy. By such action, the Consumer Technology Association does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Standard, Bulletin or other technical publication.

This document does not purport to address all safety problems associated with its use or all applicable regulatory requirements. It is the responsibility of the user of this document to establish appropriate safety and health practices and to determine the applicability of regulatory limitations before its use.

This document is copyrighted by the Consumer Technology Association and may not be reproduced, in whole or part, without written permission. Federal copyright law prohibits unauthorized reproduction of this document by any means. Organizations may obtain permission to reproduce a limited number of copies by entering into a license agreement. Requests to reproduce text, data, charts, figures or other material should be made to the Consumer Technology Association.

(Formulated under the cognizance of the CTA **R4.8 DTV Interface Subcommittee**.)

Published by
©CONSUMER TECHNOLOGY ASSOCIATION 2015
Technology & Standards Department
www.CTA.tech

All rights reserved

CONTENTS

1 Scope	1
2 References	1
2.1 Normative References	1
2.1.1 Normative Reference List	1
2.1.2 Normative Reference Acquisition	2
2.2 Informative References	2
2.2.1 Informative References discussion	2
2.2.2 Informative References List.....	2
2.2.3 Informative Reference Acquisition	2
3 General	3
4 Scanning	3
4.1 Pixel Frequency	3
4.2 Lines	3
4.3 Timing Instants	3
4.4 Progressive Systems	3
4.5 Interlaced Systems.....	3
5 System Colorimetry	3
5.1 Colorimetric Analysis and Optoelectronic Transfer	3
5.2 Wide-Gamut Color Signals	3
5.3 Linear Representation	4
5.4 Computing Nonlinear Primary Components	4
5.5 Signal Level Range.....	4
5.6 Y' Computation	4
5.7 Color-Difference Component Signals	4
6 Raster Structures	5
6.1 Vertical Timing.....	5
6.2 Frame Lines	5
6.3 Field Lines.....	5
6.4 Blanking Level	5
6.5 Clean Aperture.....	5
6.6 Sample Encroachment.....	5
7 Analog Synchronization	5
7.1 Analog Sync for the 720p Systems	5
7.1.1 Analog Sync Timing	5
7.1.2 0 _H Datum	5
7.1.3 Tri-level Sync Positive Transition	5
7.1.4 Tri-Level Sync Pulse Structure and Timing	5
7.1.5 Line Blanking Level	6
7.1.6 Frame Initiation	6
7.2 Analog Sync for the 1080i Systems	6
7.2.1 Analog Sync Timing	6
7.2.2 Positive Zero-Crossing	6
7.2.3 Positive Transition.....	6
7.2.4 Pulse Structure and Timing	6
7.2.5 Blanking Level.....	7
7.2.6 Mid-Line Tri-Level Sync Pulse.....	7
7.2.7 Interlaced System—First Field	7
7.2.8 Interlaced System—Second Field	7

- 8 Electrical Interface Specifications (720p and 1080i) 7
 - 8.1 Video Specifications 7
 - 8.1.1 Analog Interface Component Set 7
 - 8.1.2 Y' Signal and Tri-Level Sync 7
 - 8.1.3 P_B' and P_R' Signals and Bandwidth 7
 - 8.1.4 Y' Component—Reference Black and White 7
 - 8.1.5 P_B' and P_R' Components—Reference Black and Peak Color 7
 - 8.1.6 Time Coincidence 7
 - 8.2 Control Signals 7
- 9 Interface Characteristics 8
 - 9.1 Cable Impedance and Channel Numbering 8
 - 9.2 Signal Source and Termination Impedance 8
- 10 Connector and Cable 8
 - 10.1 Connector 8
 - 10.2 Cable 8
- ANNEX A Raster Apertures (Informative) 9
 - A.1.1 System 1080i Apertures 9
 - A.1.2 System 720p Apertures 9

TABLES

- Table 1 Scanning Systems 3
- Table 2 Chromaticity Coordinates 4
- Table 3 Sync Timing for 720p System 6
- Table 4 Sync Timing for 1080i System 6
- Table 5 Connector Color Code 8

FIGURES

- Figure 1 1080i Interface Vertical Timing Details 10
- Figure 2 1080i Interface Timing Relationships 11
- Figure 3 1080i Interface Horizontal Timing Details 12
- Figure 4 720p Vertical Timing 13
- Figure 5 720p Timing Relationships 14
- Figure 6 720p Levels and Timing 15

FOREWORD

This standard was developed under the auspices of the Consumer Electronics Association (CEA) Technology & Standards R4.8 DTV Interface Subcommittee.

Other analog scanning structures for analog component video interfaces are set forth in separate standards. For example, the Standard Definition TV Analog Component Video Interface is set forth in EIA/CEA-770.2-C. This standard does not address S-Video. However, since there are no CEA standards that discuss S-Video and S-Video is considered a hybrid of component the references for S-Video were placed in this document. For more information about S-Video see the following references: BS EN 60933-5:1993 or CEI IEC 933-5 in this standard's Informative Reference List.

Users of this standard should note that, at some future time, copy protection parameters, methods and/or standards are expected to be established with which copy-protected content traversing the component video interface will be required to comply.

An optional multi-pin connector, including permissible signal and pin assignments, may be specified at a later date for inclusion of audio and control signals. At that time, this standard will be revised and given a revision number and new issue date. Electrical specifications for this connector may be developed at a later date.

(This page intentionally left blank.)

HIGH DEFINITION TV ANALOG COMPONENT VIDEO INTERFACE

1 Scope

This standard defines two raster-scanning systems for the representation of stationary or moving two-dimensional images sampled temporally at a constant frame rate. The first image format specified is 1280 x 720 samples (pixels) inside a total raster of 750 lines, as given in Table 1. The second image format specified is 1920 x 1080 samples (pixels) inside a total raster of 1125 lines, as given in Table 1. Both image formats shall have an aspect ratio of 16:9. This standard specifies an analog interface having Y', P'B, P'R color encoding.

Table 1 presents all the permissible scanning systems for this standard. A compliant interface shall implement one or more of these scanning systems.

The intended uses of this interface should be:

- a) For interconnection between High Definition Television (HDTV) Receiver Decoder set top boxes and compatible television receivers or monitors.
- b) For interconnection between HDTV Digital Cable TV set top boxes (STBs) or Satellite DBS Receiver Decoders, and compatible television receivers or monitors.
- c) For interconnection of equipment to complete, self-contained analog component video systems of relatively small size.

This standard applies to signals carried on the connectors described in Section 9 and may not apply to component signals carried on other types of connectors.

Annex A (informative) contains information concerning raster apertures.

2 References

2.1 Normative References

The following references contain provisions, which, through reference in this text, constitute normative provisions of this standard. At the time of publication, the edition indicated was valid.

2.1.1 Normative Reference List

- CIE Publication 15.2 (1986), Colorimetry, Second Edition
- IEC 60169¹-8 (1978), Radio-frequency connectors, Part 8: R.F. coaxial connectors with inner diameter of outer conductor 6.5 mm (0.256 in) with bayonet lock – characteristic impedance 50 ohms (Type BNC); Amendment 2 (60169-8-am2-1997-11), Annex A (informative): Information for interface dimensions of 75 ohm characteristic impedance connector with unspecified reflection factor
- ITU-R BT.709-2, Parameter Values for the HDTV Standard for Production and International Program Exchange
- ANSI/SMPTE Standard 274M (1995), Standard for Television - 1920 X 1080 Scanning and Analog and Parallel Digital Interfaces for Multiple-Picture Rates
- ANSI/SMPTE Standard 296M (1997), Standard for Television - 1280 X 720 Scanning, Analog and Digital Representation and Analog Interface

NOTE—By permission from the Society of Motion Picture and Television Engineers, sections of this standard are directly obtained from SMPTE Standard 274M (1995) and SMPTE Standard 296M.

- SMPTE RP 177 (1993), Derivation of Basic Television Color Equations

¹ This document was formerly designated as IEC 169-8.